

© PAJ / JPO

PN - JP63297720 A 19881205

TI - DEVICE FOR AUTOMATICALLY SUPPLYING AND EXHAUSTING
LUBRICATING OIL TO AND FROM ENGINE

AB - PURPOSE: To prevent lubricating oil from degradation through the passage of
time and temperature rise by affording communication between the discharge
side of an oil pump and an oil reserving tank through a relief valve while
affording communication between the discharge side of the tank and an oil
pan through an oil replenishing device.

- CONSTITUTION: When an engine 1 is operated, an oil pump 5 interlocked with
a crankshaft 4 is operated so that lubricating oil in an oil pan 3 is taken into
respective oil paths 6a, 6b to be supplied to a section to be lubricated. And as
the rotational frequency of engine 1 is increased and the discharge pressure
of lubricating oil exceeds a set value, a relief valve 8 interposed in a relief path
6c is opened. Thus, excessive lubricating oil flows into the oil reserving tank 7
to cool lubricating oil in said tank 7. On the other hand, lubricating oil in the oil
pan 3 is decreased. When a replenishing port 9b of an oil replenishing device
9 is exposed above lubricating oil surface, lubricating oil is replenished from
the oil reserving tank 7 to the oil pan 3.

I - F01M11/06

PA - FUJI HEAVY IND LTD

IN - ISHIKAWA SUNAO

ABD - 19890330

ABV - 013130

GR - M808

AP - JP19870136839 19870529

